



Treatment Body Lotion Firm & Renew SH-02-39-07



	Ingredients	INCI Nomenclature	Suppliers	% w / w
Α	DI-Water GreenGard™ PA	Water (Aqua) Phytic Acid, Water	Green Line, LLC	qs 0.05
В	GLE Organic Glycerin Sclerothix®	Glycerin Xanthan Gum, Sclerotium Gum, Algin	Green Line, LLC Alchemy Ingredients	3.00 1.50
C1	Sucragel® XL	Glycerin, Caprylic/Capric Triglyceride, Water, Sucrose Laurate, Sucrose Stearate	Alchemy Ingredients	5.00
C2	LIPEX® Bassol C™ LIPEX® SheaSoft TR™ Glyceryl Stearate KahlWax 6290 Berry GreenSens™ IL MB Radigard™ CO-R	Brassica Campestris Seed Oil Butyrospermum Parkii (Shea) Butter Glyceryl Stearate Rhus Verniciflua Peel Wax Isoamyl Laurate Canola Oil, Rosmarinus Officinalis (Rosemary) Leaf Extract	AAK AAK Kahl Green Line, LLC Green Line, LLC	5.00 10.00 1.00 2.00 2.00 0.10
D	GreenGard™ LA BakuLipid® Biofer™ Sugar Kelp The Daydreamer ORC2500795	Water, Arginine Levulinate, Arginine Anisate Caprylic/Capric Triglyceride, Bakuchiol, Lecithin, Tocopherol Lactobacillus/Sugar Kelp Ferment Filtrate Lysate Fragrance	Green Line, LLC Lipoid Kosmetik Green Line, LLC Orchidia Fragrances	2.00 2.00 1.00 qs

100.00

5°C, room temperature

10,000 - 20,000 cPs

Brookfield DV-II (RT:

24 hours; RV T-A(91) @10 rpm)

Procedure

- 1. Add Phase A and begin mixing and heating to 70-75°C.
- Premix Phase B and add to Phase A and homogenize 3-5 minutes until gum is dispersed.
- 3. Add Phase C1 to separate mixing vessel and begin mixing.
- 4. Heat Phase C2 to 70-75°C and ensure all solids are melted. Add Phase C2 to Phase C1 very slowly for first 10-15%. Increase mixing speed as phase thickens.
- Ensure all Phases are at 70-75°C. Add Phase C and homogenize for 3-5 minutes at 3000-4000 rpm. Return to regular mixing for cooling.
- At 40°C or below, add Phase D and mix until homogeneous. Adjust pH as necessary.

How To Use

Apply and massage into clean, dry skin until absorbed. Apply twice a day for best results

3 Months	40°C		
3 Weeks	50°C		
Freeze/Thaw	3 cycles		
Physical Data			
Appearance	White to off white emulsion		
рН	5.0 – 5.5		

Stability Tested

3 Months

Viscosity



Omya Specialty Materials Inc., 5150 E. Pacific Coast Hwy. Suite 600, Long Beach, CA 90804 (877) 457-7266 | PersonalCareUS@omya.com | omyapersonalcare.us

THINKING OF TOMORROW



Omya has taken every possible care to ensure that the information herein is correct in all aspects. However, Omya cannot be held responsible for any errors or omissions which may be found herein, nor will it accept responsibility for any use which may be of the information, the same having been given in good faith, but without legal responsibility. This information does not give rise to any warranties of any kind, expressed or implied, including fitness for purpose and non-infringement of intellectual property. The technical information presented comprises typical data and should not be taken as representing a specification. Omya reserves the right to change any of the data without notice.